



Tuf-Temp® Fence



Specifications and details



Panel couplers help make set up and take down quick and easy. Panel coupler is 3-1/2" on center and 2" between uprights.


Tuf-Temp® fence footings add stability to panel connections and the thermal plastic construction helps withstand the abuses common to job sites. Coupled with anti-lift bracket, the fence is virtually impervious to trespassers.

Merchants Metals Tuf-Temp® temporary fence systems are the perfect solution for virtually any temporary fence application. The unique patented design allows for quick and easy installation and a sturdy, professional appearance.

Tuf-Temp® panels are made of galvanized welded wire which provides rigidity, strength and durability. The welded wire will not sag when installed or snag when stacked. Panels can also be easily inverted for extended use. The versatile thermoplastic fence footings have multiple positioning options and provide unmatched strength and durability.

Easy to install, transport and store, Tuf-Temp® panels provide the perfect solution to all of your temporary fence system requirements.

- Superior design and appearance provides a professional look to any job site, retail operation or event
- Panels can be inverted to extend fence life
- Lightweight (45 lbs.), stackable and snag resistant panels ensure fast installation and easy reconfiguration
- Anti-lift brackets are available for added security
- Nominal 11-1/2' length by 6-1/2' height provides design flexibility
- Frame made from 1-3/8" heavy duty .065 tubing



Welded wire grid 1-1/2" x 10-1/2"

Clean lines are the trademark of Tuf-Temp[®] fence. The weldedwire design helps deter climbing while keeping a low profile on the site. Pre-galvanized wire: 10 ga. horizontal 12 ga. vertical.



866.888.5611

An Oldcastle Company

www.merchantsmetals.com



© 2008 Merchants Metals All Rights Reserved